

BITTEL MEDIAJACK-MINI PRODUCT DATASHEET

Product Introduction

MediaJack-Mini is Bittel's latest innovation for hotels customized need for compact outlook and powerful functions Mediajack solution.

With most popular interfaces and compact outlook of 86mm * 86mm panel mountable on a standard 86mm back box, MediaJack-Mini is emerging as ideal solution for top end hotel and resorts. With wired/wireless music inputs, HDMI video inputs, dual USB chargers compatible with iPads, MediaJack-Mini is a one stop solution for guests demands for power charging, music/audio playing and movie/video watching, thus emerges as the ideal solution for both business and leisure guests.



Model: MediaJack-Mini

Material: Acrylic surface+Brushed Aluminum Alloy Frame

Color: Silver, Black, Champagne

Interfaces Illustration

- ✓ HDMI Port (HDMI 1.4)
- ✓ Stereo Bluetooth
- ✓ Mini Audio Port
- ✓ Dual USB chargers of 0.5A and 2.1 A, compatible for iPad charging.

Unique Features

- ✓ Compact outlook with only 86mm X 86mm Panel, mountable on standard BS/EU standard/86 standard back box. No need for extra back box deploying.
- ✓ Unique Acrylic panel plus brushed aluminum alloy frame with multiple colors optional for flexible customization.
- ✓ HDMI port of 1.4 protocol compatible with latest HD 1080P audio/video content.
- ✓ HDMI CEC function of HDMI input makes plug & play a snap.
- ✓ Stereo Bluetooth with A2DL features enables high definition wireless music streaming to TV.
- ✓ Direct pairing of Bluetooth without PINs gives easy usage to guests.
- ✓ Mini Audio Port for cabled audio input for more classic input connection.
- ✓ Dual USB chargers of 0.5A and 2.1 A, ready to charge all kinds of smartphones/tablets, including power-hunger iPad. Samsung/Blackberry/Apple iDevices compatible.

Dimensions and Installation

- ✓ External size: 86mm*86mm
- ✓ Internal size:64mm*58mm*45mm (L*W*D)
- ✓ DC Adapter mounting type: External.
- ✓ Mounting type: Wall mounting/desk mounting
- ✓ In-wall cables: HDMI cables, mini audio cables.

Caution: Cabling to the TV shall be done from TV side to Mediajack-Mini mounting position. PH type HDMI plugs shall be protected from rough handling.

Technical Specification

■ Supporting Format

✓ HDMI Output Format: 1080P/ (60Hz)/720P (60Hz)

✓ HDMI Input Format:

■ 480i/480P

■ 576i/576P

■ 720P (50HZ/60HZ)

■ Parameters

Power	Input AC 100V-240V/50Hz, Output DC12V 1.5A
Watt	6W
Audio/Video Input	HDMI (1.4) , Mini Audio, Stereo Bluetooth
Video Ouput	HDMI (1.4) 1080P/60Hz, Mini Audio
Communication Protocol	CEC
USB	DC5V 2.1A/DC5V 0.5A
AC Power	Same as local power
Working Environment	<p>Working Temperature: +5 °C ~ +35 °C;</p> <p>Working Humility: 25% ~ 90%</p> <p>Storage Temperature: -15 °C ~ +45 °C;</p> <p>Storage Humility: ≤80%</p> <p>Atmospheric Pressure: 86 ~ 106KPa</p> <p>Note: In order to avoid causing damages, media panel should be put in working temperature for over 3 hours before installation and use if storage temperature is lower than 5 °C.</p>